

AA-Parts
tel: +39 (0)545 41550
fax: +39 (0)545 1885119

Corso Sforza, 110 - 48010 Cotignola (Ra) Italy
email: engineering@aa-parts.com
© 2012 - AA-Parts - All right reserved

Kit content:	01	02	06	
	01	02	06	body ergal 7075 T6 High Tensile Aluminium
	01	02	06	self locking nut - nut stainless steel A2 (depending on the model)
	01	02	06	bushing Ø1,2 - Ø1,5 aluminum-bronze alloy nickel plated (depending on the model)
	01	02	06	stem M3 stainless steel AISI 316L
	01	02	06	Wire Ø1,2 - Ø1,5 stainless steel AISI 630 (depending on the model)

- ONLY FOR PRODUCT WITH SELF-LOCKING NUT**
1. Lock the stem M3 **A** in a vise equipped with protective jaws.
 2. Screw the nut M3 **B** on the rod using a 5.5 mm hex wrench.

CAUTION

The cylindrical part of the nut (the one that contains the bushing nylon) must be screwed to the first (detail **A**).

FOR ALL PRODUCTS

1. Insert the wire **C** in the bushing **D** by placing a small amount of grease between the bushing and the wire.
2. Insert the wire with the bushing in the body of the rigging screw and checking that the bushing reaches the bottom of the body (detail **B**).
3. Putting a small amount of grease on the threads of the stem M3 **F** and screw it into the body of the rigging screw.

To grease the bushing and stem recommend silicone and teflon grease.

